БАТЛАВ

ЗАСАГ ДАРГА Б.ДОРЖСҮМБЭР

СУМЫН НИЙТИЙН ЭЗЭМШЛИЙН ГУДАМЖ ТАЛБАЙГ КАМЕРЖУУЛАХ АЖЛЫН ТЕХНИКИЙН ТОДОРХОЙЛОЛТ

№	Бараа материал нэр	Тоо ширхэг	Үзүүлэлт
1	POE switch	6	**8-Port PoE Switch (дүйцхүүц)** **> Layer two commercial switch** **> Supports PoE power management** **> Supports wall-mount installation** **> Supports anti-theft lock hole** **> MAC auto learning and aging, MAC address capacity is 2K** **> Supports IEEE802.3, IEEE802.3u and IEEE802.3X standards** **> RJ45 port supports 10/100 Mbps self-adaptation** **> Supports 250 meters long distance PoE transmission** **> Conforms to IEEE802.3af and IEEE802.3at power supply standard. Port 1 supports Hi-PoE 60W power supply**
2	NVR бичигч төхөөрөмж	1	**32CH 1U 2HDDs Lite Network Video Recorder (дүйцхүүц)** **> Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.** **> Max. decoding capability: 8 × 1080p@30 fps or 2 × 8 MP@30 fps.** **> Max. 160/128/60 Mbps incoming/recording/outgoing bandwidth.** **> Supports IP cameras with a resolution up to 12 MP.** **> AI by Recorder supports 2-channel SMD Plus.** **> AI by Camera supports face detection and recognition, perimeter protection, SMD Plus, people counting, stereo analysis and heat map.** **> Supports EPTZ, and one-click arming and disarming.**
3	PTZ camera	6	**4MP 25x Starlight IR Network PTZ Camera (дүйцхүүц)** **> 1/2.8" STARVIS™ CMOS.** **> 25x optical zoom.**

			> Starlight technology. > Max. 25/30fps@4M. > IR distance up to 100 m. > Perimeter protection. > Face detection. > SMD 4.0. > IP66.
4	4k camera	12	8MP Smart Dual Light Fixed-focal Bullet Network Camera (дуйцхүүц) > 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. > Outputs max. 8 MP (3840 × 2160) @20 fps, and supports 2688×1520 (2688 × 1520) @25/30 fps.. > H.265 codec, high compression rate, ultra-low bit rate. > Built-in warm light and IR LED, the max. IR light distance is 60 m and max. warm light is 50 m. > ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments. > Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes. > Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human). > Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection. > Alarm: 1 in, 1 out; audio: 1 in, 1 out; supports max. 256 G Micro SD card; built in MIC. > 12 VDC/PoE power supply, easy for installation. > IP67, IK10 (optional) protection. > SMD Plus.
5	Утасгүй сүлжээний антенна	10	Networking interface — 1) GbE RJ45 port Power method — Passive PoE 2-pair (Pairs 4, 5+; 7, 8 Return) Power supply — 24V, 0.5A gigabit PoE adapter (Include

			Supported voltage range	20–27V DC
			Max. power consumption	8W
			Max. TX power	26 dBm
			Gain	25 dBi
			ESD/EMP protection	Air/contact: ± 24 kV
			LEDs	(1) Power, (1) LAN, (4) WLAN
			Signal Strength LEDs	Software-adjustable to correspond to custom RSSI levels
			RoHS compliance	Yes
			Salt fog test	IEC 68-2-11 (ASTM B117) Equivalent: MIL-STD-810 G method 509.5

10	Цахилгааны кабель	60m	3x2.5mm
11	6Unit rack	1	RACK 19" cabinet enables integrating CCTV, AC, I&HAS, RTV, LAN, or other systems in small companies or households. It is intended for devices manufactured in enclosures of 19" standard. Due to RACK cabinets, devices are aesthetically mounted and protected against mechanical damage
12	STP CAT5e cable	300m	Shielded (F/UTP) CAT5e Ethernet Gigabit transmission cable. Shield structure with aluminum Mylar provides noise resistance. In addition to 8 different cable colors, the lineup includes solid wire for long-distance transmission and stranded wire for easy routing. Also compliant with CAT5 (100BASE-TX) and CAT3 (10BASE-T).
13	Камер дэлгэц	1	50 inch дээш 4K TV
14	Дэлгэц тогтоогч	1	Хананд суурилуулдаг хөдөлгөөнт 50'' дээш
15	Суурилуулалт	1	Бүх хяналтын камер суурилуулж дуусгах
16	Машин механизм зардал	1	Шаардлагатай шон өндөрлөгт ажиллахад ашиглагдах машин механизмын зардал
17	Төлөвлөшгүй зардал	№	=
Нийт үнэ 40,000,000 (Дөчин сая)			